

# Miniature tension/compression force transducer

## For small measuring ranges from 10 N

### Model F2220




#### Applications

- Construction and apparatus
- Production lines, manufacturing plant
- Measurement and control facilities
- Special equipment and machinery construction
- Cable force measurements

#### Special features

- Measuring ranges 0 ... 10 N up to 0 ... 5,000 N
- Standard calibration: tension / compression (positive in tension)
- Ease of assembly
- Small geometries
- Stainless steel version



**Miniature tension/compression force transducer, model F2220**

#### Description

Miniature tension/compression force transducers are designed for static and dynamic measurement tasks in the direct flux of force. They determine the tension and compression forces in a wide scope of applications. It is possible, for example, to measure the actual force in ropes and rods.

The force is applied to this tension/compression force transducers via threaded bolts, which are located on each side of the cylindrical body.

The force transducers is available from a rated force of 10 N.

#### Note

To prevent overload, it is advantageous to connect up the force transducer electrically during installation and to monitor the measured value. In mounting the force transducer torsion and bending moments have to be avoided.

The force must be applied axial to the centre. Torsion and bending moments must be avoided.

#### Option

- High temperature version up to 250 °C
- Cable amplifier 4 ... 20 mA or DC 0 ... 10 V output
- Other cable length


## Specifications in accordance with VDI/VDE/DKD 2638

Model F2220	
Rated force $F_{nom}$ N	10 / 20 / 50 / 100 / 200 / 500 / 1,000 / 2,000 / 5,000
Relative linearity error $d_{lin}$	
Tension or compression	$\pm 0.5 \% F_{nom}$
Relative creep, 30 min.	$< \pm 0.1 \% F_{nom}$
Relative reversibility error $v$	$\pm 0.5 \% F_{nom}$
Relative deviation of zero signal $d_{s,0}$	$\pm 2 \% F_{nom}$
Relative repeatability error in unchanged mounting position $b_{rg}$	$\pm 0.1 \% F_{nom}$
Temperature effect on zero signal $TK_0$	$< \pm 0.2 \%/10\text{ K}$
Temperature effect on characteristic value $TK_C$	$< \pm 0.4 \%/10\text{ K}$
Force limit $F_L$	$150 \% F_{nom}$
Breaking force $F_B$	$> 300 \% F_{nom}$
Permissible oscillation stress acc. to DIN 50100 $F_{rb}$	$70 \% F_{nom}$
Rated displacement $s_{nom}$	$< 0.1\text{ mm}$
Material	Stainless steel
Rated temperature range $B_{T,nom}$	15 ... 70 °C (15 ... 250 °C) Others on request
Operating temperature range $B_{T,G}$	-54 ... +121 °C
Output signal (rated output) $C_{nom}$	2 mV/V (10 N 1.5 mV/V)
Input/output resistance $R_e/R_a$	350 $\Omega$
Insulation resistance	$> 2\text{ G}\Omega$
Electrical connection	Cable (PTFE) 1.5 m, open wires, 4-wire, shielded
Voltage supply	
without amplifier	DC 2 ... 5 V (max. 5 V) for mV/V output
with cable amplifier	DC 12 ... 28 V for output 0(4) ... 20 mA, DC 0 ... 10 V
Protection (acc. to IEC/EN 60529)	IP65
Weight	5 g up to 30 g depending on rated force
Calibration (standard)	Positive in tension

## Approvals

Logo	Description	Country
	<b>EU declaration of conformity</b> ■ EMC directive ■ RoHS directive	European Union
	<b>EAC (Option)</b> ■ EMC directive	Eurasian Economic Community

Dimensions



Rated force in N	Dimensions in mm				
	$\varnothing D$	H	A	B	C
10 / 20 / 50 / 100 / 200 / 500	12.7	7.4	4.8	4.6	M3 x 0.5
1,000 / 2,000 / 5,000	19.1	9.7	7.9	7.9	M6 x 1.0

Pin assignment

Electrical connection	
Excitation voltage (+)	Red
Excitation voltage (-)	Black
Signal (+)	White
Signal (-)	Green

Ordering information

Model / Rated force / Calibration direction / Connecting thread / Relative linearity error / Temperature range / Output signal / Electrical connection / Options