


General Information and Selection


HIGH-TEMPERATURE TAPES & MATERIALS



MJG-2



TFT-2



FGC-1



TFE-2

MJG-2 MYLAR® TAPE:

For gage handling with heat-curing resin systems.
1/2 in x 216 ft (13 mm x 66 m).

TFT-2 THERMOSETTING [+340°F (+170°C)] FIBERGLASS TAPE:

For electrical insulation at high temperatures.
1/2 in x 180 ft (13 mm x 55 m).

FGC-1 WOVEN FIBERGLASS CLOTH:

Bound edges. For lead anchoring when used in conjunction with M-Bond adhesives and M-Coat protective coatings. 0.015 in x 1 in x 50 yd (0.4 mm x 25 mm x 46 m).

TFE-2 HIGH MODULUS TFE TEFLON® WITH SILICONE MASTIC:

1/2 in x 108 ft (13 mm x 33 m).

CLAMPING SUPPLIES



HSC-1



HSC-2



HSC-3

HSC-1 SPRING CLAMP:

Maximum Opening: 1 in (25 mm).

Maximum Recommended Opening: 1/2 in (13 mm).

Nominal Clamp Force at Recommended Opening: 20 lbf (89 N).

HSC-2 SPRING CLAMP:

Maximum Opening: 2 in (51 mm).

Maximum Recommended Opening: 1 in (25 mm).

Nominal Clamp Force at Recommended Opening: 24 lbf (107 N).

HSC-3 SPRING CLAMP:

Maximum Opening: 3 in (76 mm).

Maximum Recommended Opening: 1-1/2 in (38 mm).

Nominal Clamp Force at Recommended Opening: 30 lbf (133 N).



GT-12



TFE-1



GT-14



SGP-2



SGP-1

GT-12 NEGATOR CONSTANT FORCE EXTENSION SPRING CLAMP:

1 x 0.006 x 38 in (25 mm x 0.4 mm x 0.97 m) stainless steel band, drum I.D. 1.16 in (30 mm), 10.6 lb (47 N) load.

TFE-1 TEFLON FILM:

0.003 in x 1 in x 50 ft (0.08 mm x 25 mm x 15 m).

GT-14 PRESSURE PADS AND BACKUP PLATES:

Kit of 12 Silicone Rubber Pads 3/32 x 1/2 x 1-1/4 in (2.5 x 13 x 32 mm), and 12 aluminum plates, 1/8 x 1/2 x 1-1/4 in (3 x 13 x 32 mm).

SGP-1 SILICONE RUBBER:

Three pieces, each 3/32 x 1 x 6 in (2.5 x 25 x 150 mm).

SGP-2 SILICONE RUBBER:

One piece, 3/32 x 6 x 6 in (2.5 x 150 x 150 mm).

Mylar and Teflon are Registered Trademarks of DuPont.