



Gage Terminals and Other Accessories

●T-type Gage Terminals

게이지 단자는 게이지 리드를 보호하기 위해 스트레인 게이지와 리드 와이어를 연결하기 위한 것입니다.
스트레인 게이지가 힘을 받는 것을 방지하고 리드선을 어느 정도 잡아 당기면 게이지 리드가 끊어지거나 벗겨지는 것을 방지합니다.

	Models	Dimensions (mm) (W × L × T*)	Materials		Packing	Operating Temperature (°C)	Recom- mended Adhesives	Remarks
			Base	Conductor				
Foil types	 T-F2B RoHS	5-pole 14×55×0.1 1-pole 14×11×0.1	Glass epoxy	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120 -55 to 120	CC-33A EP-34B	
	 T-F3B RoHS	5-pole 14×65×0.1 1-pole 14×13×0.1	Glass epoxy	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120 -55 to 120	CC-33A EP-34B	For 3-wire system
	 T-F13B RoHS	5-pole 14×65×0.3 1-pole 14×13×0.3	Glass epoxy + double-sided adhesive tape			-30 to 50	Not required	Self-bonding
	 T-F7B RoHS	5-pole 6×25×0.1 1-pole 6×5×0.1	Glass epoxy	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120 -55 to 120	CC-33A EP-34B	
	 T-F17B RoHS	5-pole 6×25×0.3 1-pole 6×5×0.3	Glass epoxy + double-sided adhesive tape			-30 to 50	Not required	Self-bonding
	 T-F8B RoHS	5-pole 4×30×0.1 1-pole 4×6×0.1	Glass epoxy	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120 -55 to 120	CC-33A EP-34B	
	 T-F10B RoHS	15×50×0.1	Glass epoxy	Copper foil	10 sheets	-196 to 120 -55 to 120	CC-33A EP-34B	Mainly for 5-element gages
	 T-F23 RoHS	5-pole 14×55×0.1 1-pole 14×11×0.1	Polyimide	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120	CC-33A	고온용
	 T-F24 RoHS	5-pole 9×40×0.1 1-pole 9×8×0.1				-55 to 200	EP-34B	
	 T-F25 RoHS	5-pole 6×25×0.1 1-pole 6×5×0.1						
	 T-F26 RoHS	5-pole 14×55×0.1 1-pole 14×11×0.1	Polyimide	Copper foil	20 sheets (5 poles/ sheet)	-196 to 350	PI-32	고온용
	 T-F27 RoHS	5-pole 9×40×0.1 1-pole 9×8×0.1						
	 T-F28 RoHS	5-pole 6×25×0.1 1-pole 6×5×0.1						
	 T-F29 RoHS	Outer: φ6 Inner: φ2.5 Thickness: Approx. 0.1	Glass epoxy	Copper foil	20 sheets	-55 to 120 Normal Temp. to 50 -196 to 120	EP-340 EP-370 CC-33A	볼트의 축방향 장력 측정용
Mold types	 T-P1	14×10×4	Styrol	Tin-plated copper wire	20 pcs	-30 to 80	CC-33A	Self-bonding
	 T-P4	14×10×4.5	Styrol + double-sided adhesive tape			-30 to 50	Not required	Self-bonding
	 T-P5	6×6×2	ABS	Tin-plated copper wire	20 pcs	-30 to 120	CC-33A	
	 T-P6	6×6×2.5	ABS + double-sided adhesive tape			-30 to 50	Not required	Self-bonding
	 T-P7	15×10×4	ABS	Tin-plated copper wire	20 pcs	-30 to 80	CC-33A	For 3-wire system
	 T-P8	15×10×4.5	ABS + double-sided adhesive tape			-30 to 50	Not required	Self-bonding
	 T-P9	6×5×4	Heat-resistant styrol	Tin-plated copper wire	40 pcs	-30 to 90	CC-33A	뒷면에 고무
	 T-P10	6×5×6	Heat-resistant styrol + rubber					

*T: 두께는 금속박을 포함합니다.