



**Features:**

- ◆ Capacity : 5~500kg
- ◆ Material: stainless steel
- ◆ Defend grade: IP66.
- ◆ Application: suitable for force control in production control, vibratory feeding equipment and other electronic weighing or force measuring fields.

Electrical connection and Dimensions:(dimension unit: mm)

**Specifications:**

capacity	kg	5,10,20,30,50,100,200,300,500
safe overload	%FS	120
ultimate overload	%FS	150
rated output	mV/V	1.5 ± 0.5
excitation voltage	Vdc	5~15
combined error	%FS	± 0.1
zero balance	%FS	± 0.1
non-linearity	%FS	± 0.1
hysteresis	%FS	± 0.1
repeatability	%FS	± 0.1
creep	%FS/30min	± 0.1
input resistance	Ω	385 ± 35
output resistance	Ω	350 ± 3
insulation resistance	M Ω	≥ 2000
operating temperature range	$^{\circ}\text{C}$	-20 ~ +65
compensated temperature range	$^{\circ}\text{C}$	-10 ~ +40
temperature coefficient of SPAN	%FS/ 10°C	± 0.1
temperature coefficient of ZERO	%FS/ 10°C	± 0.1
Electrical connection	cable	4 core shielded PVC cable, $\varnothing 3.0 \times 2\text{m}$
Wires connection	Excitation +: Red , Excitation -: Black, Output +:Green, Output -:White	

※**Ordering code:** model-capacity- rated output-accuracy-defend grade- the length of cable